



TEMPERATURE-TABLE for PTCR
Higher quality products and lower costs through Improved, reliable firing control

Type PTCR - STH				Ring Colour : Green			
Vibrantz no. : 1400606				Dimensions : ± 20 x 10 x 7,0 mm			
Temperature Range °C : 1130 - 1400°C							

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
		19,80	1129	19,30	1218	18,60	1278	18,30	1331		
		19,79	1131	19,29	1219	18,79	1279	18,29	1332		
		19,78	1133	19,28	1220	18,78	1280	18,28	1333		
		19,77	1136	19,27	1221	18,77	1281	18,27	1334		
		19,76	1138	19,26	1223	18,76	1283	18,26	1335		
		19,75	1140	19,25	1224	18,75	1284	18,25	1336		
		19,74	1142	19,24	1225	18,74	1285	18,24	1337		
		19,73	1144	19,23	1226	18,73	1286	18,23	1338		
		19,72	1147	19,22	1228	18,72	1287	18,22	1339		
		19,71	1149	19,21	1229	18,71	1288	18,21	1340		
		19,70	1151	19,20	1230	18,70	1290	18,20	1341		
		19,69	1153	19,19	1231	18,69	1291	18,19	1342		
		19,68	1155	19,18	1232	18,68	1292	18,18	1344		
		19,67	1157	19,17	1234	18,67	1293	18,17	1345		
		19,66	1159	19,16	1235	18,66	1294	18,16	1346		
		19,65	1161	19,15	1236	18,65	1295	18,15	1348		
		19,64	1163	19,14	1237	18,64	1297	18,14	1349		
		19,63	1165	19,13	1238	18,63	1298	18,13	1351		
		19,62	1167	19,12	1239	18,62	1299	18,12	1352		
		19,61	1169	19,11	1241	18,61	1300	18,11	1354		
		19,60	1171	19,10	1242	18,60	1301	18,10	1355		
		19,59	1173	19,09	1243	18,59	1302	18,09	1357		
		19,58	1175	19,08	1244	18,58	1303	18,08	1359		
		19,57	1177	19,07	1245	18,57	1304	18,07	1361		
		19,56	1179	19,06	1247	18,56	1305	18,06	1363		
		19,55	1180	19,05	1248	18,55	1306	18,05	1365		
		19,54	1182	19,04	1249	18,54	1307	18,04	1368		
		19,53	1184	19,03	1250	18,53	1308	18,03	1370		
		19,52	1185	19,02	1251	18,52	1310	18,02	1373		
		19,51	1187	19,01	1253	18,51	1311	18,01	1375		
		19,50	1189	19,00	1254	18,50	1312	18,00	1378		
		19,49	1190	18,99	1255	18,49	1313	17,99	1381		
		19,48	1192	18,98	1256	18,48	1314	17,98	1384		
		19,47	1194	18,97	1257	18,47	1315	17,97	1387		
		19,46	1195	18,96	1258	18,46	1315	17,96	1391		
		19,45	1197	18,95	1260	18,45	1316	17,95	1395		
		19,44	1198	18,94	1261	18,44	1317	17,94	1398		
		19,43	1200	18,93	1262	18,43	1318	17,93	1402		
		19,42	1201	18,92	1263	18,42	1319				
		19,41	1203	18,91	1264	18,41	1320				
		19,40	1204	18,90	1266	18,40	1321				
		19,39	1205	18,89	1267	18,39	1322				
		19,38	1207	18,88	1268	18,38	1323				
		19,37	1208	18,87	1269	18,37	1324				
		19,36	1210	18,86	1271	18,36	1325				
		19,35	1211	18,85	1272	18,35	1326				
		19,34	1212	18,84	1273	18,34	1327				
		19,33	1214	18,83	1274	18,33	1328				
		19,32	1215	18,82	1275	18,32	1329				
		19,31	1216	18,81	1277	18,31	1330				

Powder Batch # : 354	Batch approved
Date : 20/03/2025	Quality Inspection : <i>[Signature]</i>

For Inquiries :
Customer Service Desk
Phone : +49 69 27116 432
Fax : +49 69 27116 243

